



# YFK-9300A (PE blown molding)

## Specifications

|                          |                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------|
| Ingredients              | Antioxidant, auxiliary antioxidant and acid scavenger and other components in a certain proportion. |
| Appearance               | White columnar particles                                                                            |
| Volatile Loss %          | <= 2.0                                                                                              |
| Particle Size (mm)       | 2.0 ~ 3.0                                                                                           |
| Acidity Value (mg KOH/g) | <= 2.0                                                                                              |

## Usage Notes

|              |                                                                                                                                                                                                                                                                                         |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Properties   | It provides excellent oxidation resistance and long-term color protection. When used in HDPE hollow blow molding resins, the resulting material meets national technical standards. The product is environmentally friendly, heat-resistant, water-extraction resistant, and non-toxic. |
| Applications | It is a high-performance compound antioxidant designed for high-temperature processing. It provides superior processing stability and long-term color retention for polyethylene resins and is widely applicable in the production of HDPE hollow blow molding resin products.          |
| Storage      | This product is stable under normal conditions and does not have any special storage requirements. However, it should be protected from moisture and heat.                                                                                                                              |
| Packaging    | The product is packaged in cartons with plastic liners or in cardboard barrels with plastic liners. The net weight per unit is 25 kg. Customized packaging is available.                                                                                                                |